15.14 Single Detached (ZS14) – South McLennan (City Centre)

15.14.1 Purpose

The **zone** provides for **single detached housing** in Section 15-4-6.

15.14.2 Permitted Uses

housing, single detached

15.14.3 Secondary Uses

- bed and breakfast [Bylaw 8672, Jan 24/11]
- boarding and lodging
- community care facility, minor
- home business
- secondary suite

15.14.4 Permitted Density

- 1. The maximum **density** is one **principal dwelling unit**.
- 2. The maximum **floor area ratio** (FAR) is 0.55 applied to a maximum of 464.5 m² of the **lot area**, together with 0.30 applied to the balance of the **lot area** in excess of 464.5 m². [Bylaw 8816, Mar 12/12]
- 3. For the purposes of this **zone** only, the following items are not included in the calculation of maximum **floor area ratio**:
 - a) 10% of the **floor area** total calculated for the **lot** in question which must be used exclusively for covered areas of the **principal building** which are open on one or more sides and must face the **front lot line** or **rear lot line**;
 - b) 10% of the **floor area** total calculated for the **lot** in question, to a maximum of 20.0 m² provided that:
 - i) this **floor area** is located directly above a **garage**;
 - ii) this **floor area** is located directly below sloping ceilings where the ceiling is attached directly to the underside of the sloping roof and having a minimum slope of 9:12 roof pitch; and
 - the distance from the floor to the ceiling is no higher than 2.5 m measured vertically.
- 4. Notwithstanding Section 15.14.4.2, the maximum **floor area ratio** (FAR) is 0.55 for the **lot** located at: [Bylaw 8816, Mar 12/12]

9571 General Currie Road. [Bylaw 8816, Mar 12/12]

15.14.5 Permitted Lot Coverage

- 1. The maximum **lot coverage** is 45% for **buildings**.
- 2. No more than 70% of a **lot** may be occupied by **buildings**, **structures** and **non-porous** surfaces.
- 3. 25% of the **lot area** is restricted to **landscaping** with live plant material.

15.14.6 Yards & Setbacks

- 1. The minimum **front yard** is:
 - a) 6.0 m for parking pads, **garages** and **carports** provided that the maximum **garage** door width shall be the greater of 4.9 m or 50% of the **building** width; and
 - b) 6.0 m for **buildings** and **structures**.
- 2. **Bay windows** which form part of the **principal building** may project into the **front yard** for a distance of 1.0 m.
- 3. The minimum **interior side yard** is 1.2 m.
- 4. The minimum **exterior side yard** is 4.0 m.
- 5. There is no **side yard** requirement for an **accessory building** that has an area of 10.0 m² or less.
- 6. The minimum rear yard is 6.0 m. For a corner lot where the exterior side yard is 4.0 m, the rear yard is 1.2 m.
- 7. Portions of the **principal building** which are less than 2.0 m in **height**, and **accessory buildings** of more than 10.0 m², may be located within the **rear yard** but no closer than:
 - a) 6.0 m to a **lot line abutting** a public **road**; or
 - b) 0.6 m to any other **lot line**.

15.14.7 Permitted Heights

- 1. The maximum **height** for **principal buildings** is 2 ½ **storeys**, but it shall not exceed the **residential vertical lot width envelope** and the **residential vertical lot depth envelope**. For a **principal building** with a flat roof, the maximum **height** is 7.5 m. [Bylaw 9488, Mar 21/16]
- 2. The ridge line of a front roof dormer may project horizontally up to 0.9 m beyond the residential vertical lot depth envelope but no further than the front yard setback.
- 3. The ridge line of a side roof dormer may project horizontally up to 0.9 m beyond the residential vertical lot width envelope but no further than the side yard setback.

[Bylaw 9488, Mar 21/16]

4. The maximum **height** for **accessory structures** is 9.0 m.

15.14.8 Subdivision Provisions/Minimum Lot Size

- 1. The minimum **lot** dimensions and areas are as follows, except that:
 - a) the minimum **lot width** for **corner lots** is 13.0 m;
 - b) where a **lot** shares a common boundary along its **front lot line** with Ash Street or Bridge Street the minimum **lot width** is 18.0 m; and

c) where a **lot** shares a common boundary along its **front lot line** with Ash Street or Bridge Street, the minimum **lot area** shall be 550.0 m².

Minimum frontage	Minimum lot width	Minimum lot depth	Minimum lot area
n/a	11.3 m	24.0 m	320.0 m ²

15.14.9 Landscaping & Screening

- 1. **Landscaping** and **screening** shall be provided according to the provisions of Section 6.0.
- 2. A **fence** shall not be located within 6.0 m of a **road** unless:
 - a) a minimum of 30% of the total vertical area of the **fence** is open to the other side or constructed of a transparent material; and
 - b) the maximum **fence height** is 0.9 m. In the case of such a **fence**, its **height** shall be calculated as the vertical distance between the highest point on the **fence** and the greater of:
 - i) the point at which the **fence** intersects the ground; or
 - ii) the top of any curb **abutting** the property, or if there is no curb, the crown of the **adjacent road**.
- 3. The maximum **height** of a **fence** located elsewhere within a required **yard** is 2.0 m.
- 4. On a **lot** that has resulted from a single **subdivision** plan that created two or more **lots**, the **owner** shall plant and maintain three (3) trees of a minimum size of 60.0 mm calliper measured at 1.2 m above the root ball, at least one (1) of which shall be located within 6.0 m of the **front lot line**.

15.14.10 On-Site Parking and Loading

1. On-site **vehicle** parking shall be provided according to the standards set out in Section 7.0.

15.14.11 Other Regulations

1. In addition to the regulations listed above, the General Development Regulations in Section 4.0 and Specific Use Regulations in Section 5.0 apply.